

# LAFAT edge 10 comfy

KOTAO NA PELET / PELLET BOILER

## KOTAO NA PELET

Kotlovi na pelet serije EDGE su još jedan u nizu proizvoda modernog dizajna namijenjen priključenju na sistem centralnog grijanja, koji služe za zagrijavanje stambenih i poslovnih prostora uz maksimalan ugođaj korištenja. Svojom kompaktnošću i veličinom imaju veliku prednost nad kotlovima iste kategorije. Kotao posjeduje određene komponente samog sistema grijanja: cirkulaciona pumpa, ekspanziona posuda i sigurnosni ventil već ugrađene u sami kotao. Kotao posjeduje vrhunsku elektronsku regulaciju koja pruža maksimalni komfort sedmodnevnog programiranja rada kotla te odgovarajuće dodatne mogućnosti instalacije bežične kontrole kotla preko wi-fi odnosno GSM modula.

## PELLET BOILER

The EDGE series pellet boilers are another in a series of modern design products designed to be connected to a central heating system, which serve to heat residential and commercial spaces with maximum usage. Due to their compact size and size, they have a big advantage over boilers of the same category. The boiler has certain components of the heating system itself: a circulation pump, expansion vessel and safety valve already built into the boiler itself. The boiler has superior electronic control that provides maximum comfort for seven days of boiler programming and the corresponding additional options for installing wireless boiler control via wi-fi or GSM modules.





## LAFAT edge 10 comfy

Kotao na pelet / Pellet boiler

Naziv Name	Jedinica mjere Unit of measure	EDGE 10 COMFY EDGE 10 COMFY
Opseg izlazne snage min/nom Heat output range min/nom	kW	3-10
Dimenzije: Širina / Dubina / Visina Dimensions: Width / Depth / Height	mm	495x750x900
Promjer dimnjače Diameter of flue	mm	80
Grejna površina Heating surface	m <sup>2</sup>	20 - 55
Težina Weight	kg	168
Sezonski stepen iskorištenja nom/min Seasonal space energy efficiency nom/min	%	91,9/92,08
Količina vode u sistemu Amount of water in the system	l	14
min / max - Potrošnja peleta min / max - Consumption of pellets	kg/h	0,7 - 2,1
max. Dužina rada sa punim spremnikom max. Length of operation with full tank	h	27,1
min. Dužina rada sa punim spremnikom min. Length of operation with full tank	h	9
Kapacitet spremnika Pellet tank capacity	kg	19
Polazni i povratni vod Hot and return line	col	1"

\*U kotao ugrađena je cirkulaciona pumpa, ekspanzion posuda I sigurnosni ventil  
\*The boiler is equipped with a circulation pump, an expansion tank and a safety valve